

HushMeet









HushMeet is an acoustic booth that provides additional, independent space for teamwork in the office, where it is possible to conduct meetings for 4 people in comfortable conditions. Advanced acoustic solutions effectively isolate the sound. Additionally, the closed structure of the booth provides a sense of privacy. It is possible to move the entire booth without having to disassemble it. A 4-person booth takes up the same space as two standard desk workstations. The product is also available in a version for 2 people.

Features

- Upholstered interior panels available in two types of fabrics in a total of forty colours
- Speech level reduction at 28.9 dB secures privacy of conversations
- Fully automatic efficient ventilation and LED lighting system to guarantee comfort and convenience

Design by Hushoffice

HAWORTH collection







DIMENSION

Exterior size		
H: 230 cm	W: 215 cm	D: 139 cm
Interior size		
H: 201.8 cm	W: 191.6 cm	D: 132.3 cm

Acoustic laminated glass door
H: 206.7 cm W: 82.4 cm
with anodized aluminum latch handle

Acoustic laminated front side glass panels H: 207.9 cm W: 55.3 cm

Acoustic laminated rear side glass panels

H: 207.9 cm W: 78.9 cm

- clear or frosted

Tabletop H: 73.5 cm	W: 100 cm	D: 77 cm
Seat H: 45 cm	W: 132 cm	D: 40 cm
Column H: 202 cm	W: 40 cm	D: 12 cm
Weight	662 kg	

UPHOLSTERY & FINISHES

Exterior

3 layer honeycomb board, 38 mm thickness, both sides melamine covered, finished with zero-joint edge laser technology.

Interior panels

High-density LDF (HDF) 3 mm thickness, covered with non-flammable polyurethane foam, upholstered.

Glass

Acoustic, laminated safety glass (RW = 35 dB), also include the thickness 2×5 mm glass, acoustic sheet glass, safety manifestation on front.

Seat

Double-sided box-shaped couch with upholstered seat, backrest and armrest.

Tabletop

Made of 3-layer melamine chipboard.

Upholstery

40 colours of fabric for upholstered panels. Petrus: $389 \, g/m^2$, 100% PL. Wool: $325 \, g/m^2$, 70% WO, 20% PL, 5% PA, 5% AF.

Flame retardant foam (optional)

Flexible polyurethane composition, technology without using any fluorocarbons (freons), nor with volatile organic solvents (eg. methylene chloride).

Carpet

For commercial intensive use (designed for hotel room, hotel suite, boutique, shop, restaurant, reception, stairs).

Door handle and hinges

Anodized aluminum or aluminum painted in dark gray.

FEATURES AND SPECIFICATIONS

Air ventilation system

Motion sensor activated, 6 fans, maximum performance of the single fan – $58~m^3/h$, total air change – $348~m^3/h$.

Electrification

LED ceiling light. Lighting power: 19,2 W/1940 lm.

Power module (power 230V, USB Type A/C, 2 x RJ45).

Motion sensor activated. Max. power consumption: 49.5 W.

ACOUSTICS

Results according to ISO 23351-1:2020. Speech level reduction – D_{SA} 28.9 (dB).

SEISMIC ANCHORAGE

All Hushoffice products come with Seismic Anchoring capability as standard solution.