

HushTwin




HushTwin consists of two independent acoustic booths connected to each other, each equipped with a separate sofa, an independent table and a separate lighting and ventilation system. HushTwin takes up less than 2 sqm, thanks to which it will fit into almost any office space. HushTwin consists of two independent spaces, each equipped with an electric socket and a manually controlled lighting and ventilation system. It is possible to move the entire booth without having to disassemble it.

Features

- Upholstered interior panels available in two types of fabrics in a total of forty colours
- Speech level reduction secures privacy of conversations
- Fully automatic efficient ventilation and LED lighting system to guarantee comfort and convenience

Design by
Hushoffice



DIMENSION

Exterior size		
H: 230 cm	W: 215 cm	D: 90 cm
Interior size (single space)		
H: 202 cm	W: 93.7 cm x 2	D: 83 cm

Acoustic laminated glass door		
H: 206.7 cm	W: 95.4 cm	
with anodized aluminum latch handle		

Acoustic laminated rear side glass panels		
H: 207.9 cm	W: 96.8 cm	
- clear or frosted		

Tabletop		
H: 71 cm	W: 79.2 cm	D: 30 cm

Seat		
H: 45 cm	W: 83 cm	D: 40 cm

Weight	537 kg
--------	--------

ACOUSTICS

Acoustic principles



Low Tones



Mid Tones



High Tones

Acoustic performance



Absorption



Attenuation



Diffusion

UPHOLSTERY & FINISHES

Exterior

3 layer honeycomb board, 38 mm thickness, both sides melamine covered, finished with zero-joint edge laser technology.

Interior panels

High-density LDF (HDF) 3 mm thickness, covered with non-flammable polyurethane foam, upholstered.

Glass

Acoustic, laminated safety glass (RW = 35 dB), also include the thickness 2 x 5 mm glass, acoustic sheet glass, safety manifestation on front.

Seat

Double-sided box-shaped couch with upholstered seat, backrest and armrest.

Tabletop

Made of 3-layer melamine chipboard.

Upholstery

40 colours of fabric for upholstered panels.

Petrus: 389 g/m², 100%PL.

Wool: 325 g/m², 70%WO, 20%PL, 5%PA, 5%AF.

Flame retardant foam (optional)

Flexible polyurethane composition, technology without using any fluorocarbons (freons), nor with volatile organic solvents (eg. methylene chloride).

Carpet

For commercial intensive use (designed for hotel room, hotel suite, boutique, shop, restaurant, reception, stairs).

Door handle and hinges

Anodized aluminum or aluminum painted in dark gray.

FEATURES AND SPECIFICATIONS

Air ventilation system

Motion sensor activated, 6 fans, maximum performance of the single fan – 47 m³/h, total air change – 282 m³/h.

Electrification

LED ceiling light. Lighting power: 6.4 W/284 lm.

Power module 2 x (power 230V, USB Type A, RJ45).

Motion sensor activated. Max. power consumption: 30 W.

SEISMIC ANCHORAGE

All Hushoffice products come with Seismic Anchoring capability as standard solution.