

TECHNICAL SPECIFICATION

hushphone HUS-BX-218

OFFICE PHONE CALLS HAVE NEVER BEEN SO COMFORTABLE

Modern workplaces are adapting to the needs of the people who perform their jobs in them. Providing special zones for phone calls and videoconferences has become one of the crucial elements of an office that is friendly and open to the needs of employees. The best solutions should be flexible and inexpensive to implement, and this is exactly what we provide.



DIMENSIONING




1


W/D/H: exterior 41.33 x 35.43 x 87.79 in
interior 32.28 x 32.55 x 79.92 in

Weight: 745 lbs **Weight with crate:** 943 lbs


Logistic data is available on request.



1 Cutout for sprinkler installation 2 Power cable access



3 Stool (optional)



4 Preparation for the stool assembly



ELECTRIFICATION


LED ceiling light.

Power module: UL standard: 1x (power, USB Type A 2.4A, USB Type C 5A).
Black color.

Motion sensor: activating lighting and airflow at 100% power. Located under the rear shelf. Standby power consumption 0.3 W.

Maximum power consumption of the product 7 W.

Power cable: access from ceiling or base (detailed information can be found in the Assembly Manual). 2.36 in milling prepared from the inside of the ceiling (not visible from outside). White cable with three-prong grounded plug 110V. The total length of the cable – 14.78 ft. The cable length for the exit of unit – 11.82 ft.



5 Power module



LIGHTING


Ceiling light 2.5 W/160 lm. 4000 K. Avg. [lux] 32. Min. [lux] 29 Max. [lux] 34.*

* Calculation results of the LED light source on the tabletop inside the booth.
The final amount of Lux depends on the lighting intensity in the office space.



VENTILATION

2 fans. 4238 ft³/h* / 80 seconds**.



* maximum performance of the single fan, taking into account losses in the ventilation system.
** total time of air change inside based on the volume and capacity of one fan.



hushoffice

Manufacturer: Fabryka Mebli Biurowych Mikomax sp. z o.o. | 93-231 Łódź ul. Dostawcza 4, Polska
Distributor: Mikomax sp. z o.o. | 93-231 Łódź ul. Dostawcza 4, Polska

hushoffice.com

TECHNICAL SPECIFICATION

hushphone HUS-BX-218

EXTERIOR

GLASS DOOR with LATCH HANDLE: acoustic, tempered and laminated safety glass 0.39 in, 5.5.2 thickness including the thickness of 0.19 in glass, 0.07 in acoustic sheet and 0.19 in glass. Clear color.

REAR SIDE GLASS PANEL: acoustic and laminated glass 0.39 in (RW= 35 dB), 5.5.2 thickness including the thickness of 0.19 in glass, 0.07 in acoustic sheet and 0.19 in glass. Placed in aluminum profiles with acoustic seal. Clear color.

PROFILES: for glass and door frame in cosmos grey color.

DOOR HANDLE AND HINGES: anodized aluminum or aluminum painted in cosmos grey color.

CASE: 3-layer honeycomb board with a thickness of 1.49 in. Both sides covered with melamine and finished with ABS edging.

Integrated castors with levelling feet.

2.50 in hole with grommet for sprinkler installation.

INTERIOR

Side FOLD-AWAY LAPTOP TABLE (with leather handle).
Dimension: 18.42 x 12.99 in. Opened from the side wall. Made of natural veneer, melamine or non-finger laminate. Maksimum load – **3 kg** (6.61 lbs).

Ergonomic MDF tapered **REAR SHELF** 32.28 x 6.06 – 8.42 x 10.86 in.
Maximum load on the upper shelf – **10 kg** / 22 lbs.
Maximum load on the lower shelf – **5 kg** / 11 lbs.

STOOL (optional): Base made of steel, powder in cosmos grey color. Column adjustment range: 9.8 in. Min. height 24.8 in. Max. height 34.6 in. Footrest integrated with the column. Seat frame made of LDF. Upholstered with the use of 17.70 in foam layer. Maximum load 100 kg (264.55 lbs).

INTERIOR PANELS: high-density LDF (HDF) 0.12 in thickness, covered with non-flammable polyurethane foam. Upholstered.

FLAME RETARDANT FOAM: complies with BS 5852: Part 2: 1982, Ignition source 5 (Crib 5).

UPHOLSTERY Wool:

weight: 325 g/m², **composition:** 70%WO, 20%PL, 5%PA, 5%AF, **flammability:** cigarette and match (BS-EN 1021-1, 2) (BS 5852-0, 1), CAL 117 (class 1), ASTM 84 (class 1), **light fastness:** 5 (EN ISO 105B02), **fastness to rubbing:** wet: 4/5; dry: 4/5 (ISO 105-X12), **abrasion resistance:** 100.000 martindale cycles (EN ISO 12947-2).

INTEGRAL CARPETED FLOOR.

CARPET: complies with ASTM D2859 – 16 (2021), standard test method for ignitability characteristics of finished textile floor covering materials. Adapted to commercial intensive use (hotel room, hotel suite, boutique, shop, restaurant, conference room, high traffic office, reception, stairs). Graphite color.

ACOUSTIC RATING

Frequency range 125 Hz to 8000 Hz according to ISO 23351-1:2020. Speech level reduction – D_{sA} 24.7 (dB).

SEISMIC ANCHORAGE

Product with Seismic Anchoring capability as standard solution. Instructions on how to anchor are available on request.

SUSTAINABILITY

Hushoffice booths are manufactured in a ISO 9001 and 14001 certified production facility in Poland by Mikomax Smart Office. They are compliant with the ISO 14001 Environmental Management System Standard. Hushoffice is packed and delivered in light cardboard boxes which are recycle-friendly.

CERTIFICATION



Warranty



Made in EU



Premium wool
CAL 117



Certificates



hushoffice

Manufacturer: Fabryka Mebli Biurowych Mikomax sp. z o.o. | 93-231 Łódź ul. Dostawcza 4, Polska
Distributor: Mikomax sp. z o.o. | 93-231 Łódź ul. Dostawcza 4, Polska

hushoffice.com